





Backer Series 3



ACGI Grille Systems feature two categories—Grille Backer Series (GB) and Grille Dowel Series (GD). Both systems are available in solid wood or wood veneer (depending on blade size and design requirements). Blade sizes are typically 1 $\frac{3}{8}$ "–3 $\frac{1}{2}$ " deep (for depths greater than 3 $\frac{1}{2}$ " see our Baffle Systems). Grille panels are typically assembled with four to ten blades per foot. Panels are nominal 1' or 2' wide by varying lengths in 1' increments (custom widths and lengths are available).

Grille Backer Series 3 [GB3] is similar to GB1, however GB3 panels "lay into" HD T-grid and do not usually require screws or clips. GB3 is panelized using a solid wood backer at 12" O.C. The backers are typically painted flat black, but are available in other colors. The blade depth is typically 1-1/2," and panels are nominal 2' wide by 2' or 4' length. The reveal size at the panel edge matches the size of the 15/16" grid. Optional notched backers provide additional strength and stability for wall applications with blade depths greater than 2". Like most of our other systems, GB3 panels allow for post-installation access to the plenum.



Grille Backer Series 1 — Specification Information

Product No.	Suspension	Encapsulated Insulation	Blades per ft.	Depth	Typical Thickness
GB3-####-#	Wood Backer	No	4-10	1"-3½"	¾"

How To Spec It...

Series Thickness ●

GB3-8150-C


Blades per ft. Depth

What It Means... Grille Backer Series 3 with 8 blades per foot, 1½" blade depth, and ¾" thickness.


Thickness Reference

A	½"
B	⅝"
C	¾"
D	⅞"
E	1"
F	1⅛"
G	1¼"
H	1⅝"
I	1½"
J	1⅞"
K	1¾"
L	1⅞"
M	2"
N	2⅛"
O	2¼"
P	2⅜"

Square Blade Profile



Radiused Blade Profile



ACOUSTICS

NRC of 0.60 (1" insulation)

NRC of 0.80 (2" insulation)

Grille panels are a traditional product offering the warmth of wood plus acoustical treatment. A large amount of open area allows sound to pass unobstructed into the plenum space and/or acoustic insulation behind the panels. Consequently, acoustical performance of a wood grille is determined by the properties of the absorbing medium. This medium is often fiberglass insulation in bags, mats, or duct liner.

LEED® CREDIT

MR 4.1, MR 4.2, MR 7, EQ 4.4

SPECIES + STAINS

For this product ACGI can source any commercially available solid wood and apply any standard, color-matched or custom finish. Contact us for details.

FIRE RATING

Solid wood finishes and both veneer finishes and cores can be provided with a Class A fire rating [ASTM-E84].

DELIVERY, STORAGE & HANDLING

Material must be stored and installed only in secured ambient environment (humidity range 25%–55%, temperature not to exceed 86°F). All windows, doors and wet-work must be complete before installation. Handle carefully to avoid damaging.

WARRANTY

All materials supplied by ACGI are guaranteed against manufacturing defects for one year. Wood stains and colorings can vary over time due to job site conditions and are therefore excluded from this warranty. The contractor shall warrant for one year all work from final acceptance of completed work.

